



MDSA Series



SMD Low Profile High Current Molded Inductor

Size 7050


FEATURES

- Shielded construction
- Capable of corresponding high frequency .
- Low loss realized with low DCR.
- High performance (Isat) realized by metal dust core.
- Ultra low buzz noise, due to composite construction.
- 100% Lead(Pb)-Free and RoHS compliant.
- AEC-Q200 qualified
- Operating temperature: -55 to +155 °C (including self-temperature rise)
-

Dimensions: [mm]



Land Pattern: [mm]



Electrical Properties:

Part Number	Inductance (mH)	DCR (mΩ)	Isat (A)	Q	Temperature Coefficient (%)
MDSA7050-1R0M	1.00				
MDSA7050-1R5M	1.50				
MDSA7050-2R2M	2.20				
MDSA7050-3R3M	3.30				
MDSA7050-4R7M	4.70				
MDSA7050-5R6M	5.60				
MDSA7050-6R8M	6.80				
MDSA7050-8R2M	8.20				



MDSA7050-100M	10.0	±20%	6.6	5.6	45.0	54.0
MDSA7050-150M	15.0	±20%	4.7	3.8	74.0	86.0
MDSA7050-220M	22.0	±20%	4.0	3.4	124	144
MDSA7050-330M	33.0	±20%	2.8	2.0	145	172
MDSA7050-470M	47.0	±20%	2.5	1.7	278	325

Saturation Current will cause L to drop approximately 30%

Temperature Rise Current: The actual value of DC current when the temperature rise is $\Delta T=40^{\circ}\text{C}$

Typical Electrical Characteristics:

